

PRODUCT DATA SHEET



SOFT TOUCH

AVAILABLE COLOURS

D10 White
D40 Black
D60 Anthracite
D80 Blackblue

Additional colours on request with minimum order quantity and a longer delivery time.

SURFACE CHARACTERISTICS

- Matt
- Anti-Fingerprint
- Scratch resistant

For horizontal and vertical indoor use.

AVAILABILITY / SIZES / THICKNESSES

MDF direct coating in E1 quality

Size (mm) / Thickness (mm)	2440 x 1220	3050 x 1220	3660 x 1220
12	X	X	X
15	X	X	
16	X	X	
18	X	X	X
19		X	
22	X	X	
25		X	
28		X	
50			X

Coating options:

- One side décor coating with surface protection film / back side balancing material
- Both sides décor coating with surface protection film

Special MDF qualities like black core, resistant to humidity, fire retardant, carb II as well as additional sizes as per customer requirement available on request with minimum order quantity and a longer delivery time.



AVAILABILITY / SIZES / THICKNESSES

Laminate

in the size 3050 x 1300 x 0,8 mm with surface protection film

Composite element

in the size 3050 x 1300 / 1270 / 1250 / 1220 mm depending on chosen substrate (chipboard or MDF)

Coating options:

- One side laminate coating with surface protection film / back side balancing material
- Both sides laminate coating with surface protection film

Edging material

available in different thicknesses and widths

NO WHITENING EFFECT ON THE SURFACE DURING MILLING OF THE EDGING MATERIAL !!!

TECHNICAL DATA (Extract)

Scratch resistance	as per EN 438-2:2016 grade 3
Abrasion resistance	as per EN 438-2:2016 IP = 150 rotations
Chemical resistance	as per EN 438-2:2016 group 1,3 – grade 5, no visible change group 2 - grade 2, significant change
Steam resistance	as per EN 438-2:2016 grade 5, no visible change

Further technical data on request.